


J16120 S-RACE® Photo Panel Pro 120

Microporous Coated Sublimation Paper

Printability

- simplex printable



Product Specification

| Property | Test Method | Dimension | Target | Tolerance |
|-----------|----------------|------------------|--------|-----------|
| Weight | DIN EN ISO 536 | g/m ² | 120 | ± 5 |
| Thickness | DIN EN ISO 534 | µm | 148 | ± 6 |
| | DIN EN ISO 536 | mil | 5.8 | ± 0.25 |

Printing Technology

-  Sublimation water-based systems

Certificates

- FSC on request

Key Applications

- Large ChromaLuxe plates (hard Substrates)
- Especially designed for photo panels or other rigid substrates
- Developed jointly with Universal Woods and their brand ChromaLuxe®
- Created for professional large format printers to handle small and large size ChromaLuxe® applications

Benefits & Properties

- Perfectly matched components for reliable results
- No crumbling of paper at the edges
- Richer and more vibrant colours
- Deeper and non-cloudy black
- Homogeneous colors
- Excellent line sharpness

Version: 08/2023

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

This is not a commercial specification, but a technical data sheet that describes the main characteristic of the making. Modifications reserved. In case of question, please contact the Felix Schoeller product management.

felix-schoeller.com



FELIX SCHOELLER