

# TECHNICAL DATA SHEET



## S-RACE® Tacky 100

Product line: S-RACE® Select

Grade: J30100

Microporous Pigment Coated Thermal Adhesive Dye Sublimation Paper

### Product specification\*

Grammage: 100 g/m<sup>2</sup> ± 6 g/m<sup>2</sup>  
Thickness: 127 µm ± 6 µm  
5.0 mil ± 0.25 mil

### Benefits

- › Optimal tack between paper and fabric during sublimation transfer (no ghosting)
- › Extremely fast drying
- › Excellent line sharpness
- › Superb and quick transfer properties
- › Outstanding lay-flat performance
- › Exceptional quality consistency

This product is fully recyclable.

### Key applications

- › Transfer on all kinds of polyester textiles
- › Especially designed for elastic textiles. No movement between paper and fabric during transfer (eliminates possible ghosting effect)
- › For medium to high ink coverage

Width (cm)	Roll diameter (mm)	Core (inch)
61.0	120   –   –   –   –   –   –   –	3
111.8	–   150   170   250   300   400   500   1000	3
162.0	–   150   170   250   300   400   500   1000	3

*Other specifications on request.*

*Please note: the outer side of the roll is the printing side.*

#### Storage

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\*Modifications reserved.