

TECHNICAL DATA SHEET

S-RACE® Vivid I20

Grade: J15120

Microporous Coated Dye Sublimation Paper

Product specification*

Grammage: 120 g/m² ± 6 g/m²
Thickness: 147 µm ± 6 µm
5.8 mil ± 0.25 mil

Benefits

- › Brilliant image quality
- › Extremely fast drying
- › Excellent line sharpness
- › Superb and quick transfer properties
- › Outstanding lay-flat performance
- › Exceptional quality consistency

Key applications

- › For all dye sublimation desktop printers (such as Sawgrass, Epson or Ricoh) and large format printers
- › Especially designed for fabrics used in the soft signage; for sublimation onto photo panels and merchandise, interior and architecture articles
- › Transfer on photo panels (e.g. ChromaLuxe®), ceramic mugs or tiles, polyester-coated hard substrates such as glass, fibreglass, boards, etc. and mouse pads as well as polyester textiles

ROLLS

Width (cm)	Roll diameter (mm)	Core (inch)
33.0	120 – – –	2
43.2	120 – – –	2
61.0	120 – – –	2
63.0	120 – – –	2
132.0	– 150 170 1000	3
162.0	– 150 170 1000	3

SHEETS

Size	Sheets per Box
Mugsize**	250 1000
A4	100 200 1000
A3	100 200 1000
A3+	100 200 1000

Other specifications on request.

Please note: the outer side of the roll is the printing side.

Storage

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

*Modifications reserved.

**Mugsize: 10 cm x 24 cm

www.s-race.com

S-RACE®