TECHNICAL DATA SHEET

S-RACE® Dynamic 38
Product line: S-RACE® Dynamic
Grade: E10038
Microporous Coated Dye Sublimation Paper

Product specification*

Grammage:	38 g/m²	± 6 g/m²
Thickness:	51 µm	± 6 µm
	2.0 mil	± 0.25 mil

Benefits

- Extremely fast drying
- Excellent line sharpness
- Superb and quick transfer properties
- Outstanding lay-flat performance
- Exceptional quality consistency
- Protect from ink strike through
- Easy qualification on the printing machine

This product is fully recyclable and biodegradable.

Key applications

- Transfer on all kinds of polyester textiles
- Especially designed for high speed and large volume printing applications
- Recommended for sublimation onto fabrics used in the fashion and home decor market
- For low to medium ink coverage

Width (cm)	Roll diameter (mm)	Core (inch)
162.0	170 | 300 | 400 | 1000	3

Other specifications on request.
Please note: the outer side of the roll is the printing side.

Storage
Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

*Modifications reserved.

www.s-race.com

S-RACE®

Version 10/2021