

TECHNICAL DATA SHEET



S-RACE® Dynamic 60

Product line: S-RACE® Dynamic

Grade: E10060

Microporous Organic Coated Dye Sublimation Paper

Product specification*

Grammage: 60 g/m² ± 6 g/m²

Thickness: 74 µm ± 6 µm

2,9 mil ± 0.25 mil

Benefits

- › Extremely fast drying
- › Excellent line sharpness
- › Superb and quick transfer properties
- › Outstanding lay-flat performance
- › Exceptional quality consistency
- › Protect from ink strike through
- › Easy qualification on the printing machine

Key applications

- › Transfer on all kinds of polyester textiles
- › Especially designed for high speed and large volume printing applications
- › Recommended for sublimation onto fabrics used in the fashion and home decor market
- › Also suitable for applications in the sportswear and soft signage market
- › For low to medium ink coverage

This product is fully recyclable and biodegradable.

Width (cm)	Roll diameter (mm)	Core (inch)
162.0	170 – 300 400 1000	3
180.0	– – 300 400 1000	3
182.9	– – 300 400 1000	3
320.0	– 190 300 400 1000	3

Other specifications on request.

Please note: the outer side of the roll is the printing side.

Storage

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

*Modifications reserved.

www.s-race.com

S-RACE®