


J15105 S-RACE® Allround 100

Microporous Coated Sublimation Paper

Printability

- simplex printable



Product Specification

| Property | Test Method | Dimension | Target | Tolerance |
|-----------|----------------|------------------|--------|-----------|
| Weight | DIN EN ISO 536 | g/m ² | 100 | ± 5 |
| Thickness | DIN EN ISO 534 | µm | 125 | ± 6 |
| | DIN EN ISO 536 | mil | 4.9 | ± 0.25 |

Printing Technology

-  Sublimation water-based systems

Certificates

- FSC on request

Key Applications

- Transfer on all kinds of polyester materials (soft and hard substrates)
- Designed for all kind of textile applications such as sportswear or signage.
- For medium to high ink coverage

Benefits & Properties

- Extremely fast drying
- Excellent line sharpness
- Superb and quick transfer properties
- Outstanding lay-flat performance
- Exceptional quality consistency
- Suitable for soft and hard substrates

Version: 08/2023

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

This is not a commercial specification, but a technical data sheet that describes the main characteristic of the making. Modifications reserved. In case of question, please contact the Felix Schoeller product management.

felix-schoeller.com



FELIX SCHOELLER