

J15105 S-RACE® Allround 100 Matt 100

Microporous Coated Sublimation Paper


Printability

- simplex printable

Product Specification

Property	Test Method	Dimension	Target	Tolerance
Weight	DIN EN ISO 536	g/m ²	100	± 5
Thickness	DIN EN ISO 534	µm	125	± 6
	DIN EN ISO 536	mil	4.9	± 0.25

Printing Technology

-  Sublimation water-based systems

Certificates

- FSC on request

Key Applications

- Transfer on all kinds of polyester materials (soft and hard substrates)
- Especially designed for sportswear, banners, flags, skis and snowboards
- For medium to high ink coverage

Benefits & Properties

- Extremely fast drying
- Excellent line sharpness
- Superb and quick transfer properties
- Outstanding lay-flat performance
- Exceptional quality consistency
- Suitable for soft and hard substrates

Version: 08/2023

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

This is not a commercial specification, but a technical data sheet that describes the main characteristic of the making. Modifications reserved. In case of question, please contact the Felix Schoeller product management.

felix-schoeller.com



FELIX SCHOELLER