

# TECHNICAL DATA SHEET



J30080 | S-RACE® tacky | 80 g/m<sup>2</sup>  
Microporous Coated Sublimation Paper

## PRODUCT SPECIFICATION\*

Grammage	80 g/m <sup>2</sup> ± 6 g/m <sup>2</sup>
Thickness	100 µm ± 6 µm 4.0 mil ± 0.25 mil

## KEY APPLICATIONS

- › Transfer on all kinds of polyester materials
- › Especially designed for elastic textiles, no movement between paper and fabric during transfer (eliminates possible ghosting effect)
- › With optimised barrier properties
- › For medium to high ink coverage

## BENEFITS & PROPERTIES

- › Optimal tack between paper and fabric during sublimation transfer (no ghosting)
- › Extremely fast drying
- › Excellent line sharpness
- › Superb and quick transfer properties
- › Outstanding lay-flat performance
- › No ink strike-through
- › Exceptional quality consistency

## S-RACE® tacky J30080

Width (cm)	Roll length (m)	Core	Roll diameter (mm)
111.8	100   170	3 Inch	150   170
132.0	170	3 Inch	170
162.0	170   380   575   1100   1800	3 Inch	170   250   300   400   500
182.9	170   380   575   1100   1800	3 Inch	170   250   300   400   500
190.0	600   1100   1800	3 Inch	300   400   500

Further widths, lengths and core sizes are available on request, also jumbo rolls.

**i** Please note: the outer side of the roll (yellowish side) is the printing side. Don't print on the brighter side!

### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH).  
Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

Version 11/2017