

# TECHNICAL DATA SHEET



J15130 | S-RACE® | 130 g/m<sup>2</sup>  
Microporous Coated Sublimation Paper

## PRODUCT SPECIFICATION\*

Grammage	130 g/m <sup>2</sup> ± 6 g/m <sup>2</sup>
Thickness	152 µm ± 6 µm 6.0 mil ± 0.25 mil

## KEY APPLICATIONS

- › Transfer on all kinds of polyester materials (soft and hard substrates)
- › Especially designed for fabrics used in the soft signage and display market
- › Very high ink coverage and deep colours possible

## BENEFITS & PROPERTIES

- › Extremely fast drying
- › Excellent line sharpness
- › Superb and quick transfer properties
- › Outstanding lay-flat performance
- › Exceptional quality consistency
- › Suitable for soft and hard substrates

## S-RACE® J15130

Width (cm)	Roll length (m)	Core	Roll diameter (mm)
111.8	75   110	3 Inch	150   170
132.0	110	3 Inch	170
162.0	110	3 Inch	170
182.9	110	3 Inch	170

Further widths, lengths and core sizes are available on request, also jumbo rolls.

**i** Please note: the outer side of the roll (yellowish side) is the printing side. Don't print on the brighter side!

### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH).  
Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

Version 08/2017