

TECHNICAL DATA SHEET



J20080 | S-RACE® | 80 g/m²
Microporous Coated Sublimation Paper

PRODUCT SPECIFICATION*

Grammage	80 g/m ² ± 6 g/m ²
Thickness	100 µm ± 6 µm 4.0 mil ± 0.25 mil

KEY APPLICATIONS

- › Transfer on all kinds of polyester materials
- › Especially designed for sublimation onto fabrics used in sportswear and soft signage, with optimised barrier properties (not recommended for hard substrates)
- › For medium to high ink coverage

BENEFITS & PROPERTIES

- › Extremely fast drying
- › Excellent line sharpness
- › Superb and quick transfer properties
- › Outstanding lay-flat performance
- › No ink strike-through
- › Exceptional quality consistency

S-RACE® J20080

Width (cm)	Roll length (m)	Core	Roll diameter (mm)
111.8	100 170	3 Inch	150 170
132.0	170	3 Inch	170
162.0	170 380 575 1050 1750	3 Inch	170 250 300 400 500
182.9	170 380 575 1050 1750	3 Inch	170 250 300 400 500
190.0	575 1050 1750	3 Inch	300 400 500

Further widths, lengths and core sizes are available on request, also jumbo rolls.

i Please note: the outer side of the roll (yellowish side) is the printing side. Don't print on the brighter side!

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 01/2019